


SOTTILE40

DUE



Housing	Aluminium, die cast
RAL colour	9004 (Black), 9003 (White), 1036 (Gold)
Fixture type	Surface mounted
Module	Bridgelux V10
Driver	TRIAC dimmable driver
Lumen output	500lm, 700lm
CCT	2700K, DTW (3000K – 2000K)
CRI	>90Ra
Beam angles	15°, 24°, 40°
Rotatable	350°
Tiltable	90°
Expected Lifetime	50.000h L80/B10
Photobiological safety	RG1 unlimited
Power factor	> 0.9
Colour consistency	3 SDCM
Warranty	3 years warranty on LED module and driver

LED MODULES

Standard DTW

OPTIONS

LED MODULE OPTIONS

Description	Lumen	Watt	Lm/W	CCT	CRI
Bridgelux V10	1100Lm	15W	73	927, 930	>90Ra
Bridgelux V10 DTW	1100Lm	15W	73	(3000K – 2000K)	>90Ra

Net Weight	Dimensions carton L x W x H	Qty outer carton
On request	On request	On request

LED modules

Standard: CRI>80 and >90 in CCT 2700K, 3000K, 3500K, 4000K

Premium White (PW): for fresh white and depth of colour in retail environments

¹⁾ Lumen output of LED module (COB)

²⁾ Mentioned wattage applies for the COB only. Mentioned wattage applies for the most efficient CCT.

The power of the complete fixture will be slightly higher due to the power consumption of the driver.

³⁾ Values shown are average values and are subject to +/- 10% tolerance (set by international standards). The colour temperature is subject to a tolerance of up to +/- 150 Kelvin compared to the nominal value. Technical data can be changed by Louis MMXXII without prior notice.